

VENDED LAUNDRY

ECO-Line Tumble Dryers and Stack Tumble Dryers

11.3 kg Tumble Dryer
13.6 kg Tumble Dryer
15.9 kg Tumble Dryer
24.9 kg Tumble Dryer

34.0 kg Tumble Dryer
13.6 kg Stack Tumble Dryer
20.4 kg Stack Tumble Dryer

Speed Queen®



ECO 



VENDED LAUNDRY ECO-LINE TUMBLE DRYERS 11.3-34.0 KG

	ST025	ST030	ST035	ST055	ST075	STT30	STT45
Capacity - kg (lb)	11.3 (25)	13.6 (30)	15.9 (35)	24.9 (55)	34.0 (75)	13.6 (2x30)	20.4 (2x45)
Width - mm (in)	711 (28)	711 (28)	800 (31 1/2)	876 (34 1/2)	981 (38 5/8)	800 (31 1/2)	876 (34 1/2)
Depth - mm (in)	1038 (40 7/8)	1191 (46 7/8)	1191 (46 7/8)	1362 (53 5/8)	1378 (54 1/4)	1086 (42 3/4)	1235 (48 5/8)
Height - mm (in)	1622 (63 7/8)	1622 (63 7/8)	1622 (63 7/8)	1695 (66 3/4)	1946 (76 5/8)	1937 (76 1/4)	2059 (81 1/16)
Cylinder Diameter - mm (in)	673 (26 1/2)	673 (26 1/2)	762 (30)	838 (33)	939 (37)	762 (30)	838 (33)
Cylinder Depth - mm (in)	610 (24)	762 (30)	762 (30)	889 (35)	914 (36)	660 (26)	762 (30)
Cylinder Volume - liters (cfm)	217 (7.7)	271 (9.6)	347 (12.3)	491 (17.3)	634 (22.4)	301 (10.6)	421 (14.8)
Reversing Cylinder	Option	Option	Option	Option	Option	N/A	N/A
Door Opening Size - mm (in)	576 (22 11/16)	576 (22 11/16)	576 (22 11/16)	683 (26 57/64)	683 (26 57/64)	576 (22 11/16)	683 (26 57/64)
Energy data - kW (Btu/hr)							
Gas Models - 60 Hz	15.4 (52K)	16.1 (55K)	18.7 (64K)	30.8 (105K)	38 (130K)	16.1 (55K)	23.5 (80K)
Gas Models - 50 Hz	13.2 (45K)	15.4 (52K)	16.1 (55K)	26.4 (90K)	32.2 (110K)	15.4 (52K)	21.7 (74K)
Electric Models	9 kW	12 kW	12 kW	18 kW	21 kW	12 kW	N/A
Gas Connections - mm (in)	13 (1/2) NPT	13 (1/2) NPT	13 (1/2) NPT	13 (1/2) NPT	13 (1/2) NPT	13 (1/2) NPT	13 (1/2) NPT
Air Outlet Diameter - mm (in)	102 (4)	152 (6)	152 (6)	203 (8)	203 (8)	152 (1 x 6)	254 (1 x 10)
Motor - HP (Rev)	1/4 (N/A)	1/4	1/4	1/2	1/2	2 x 1/4	2 x 1/2
Airflow 60 Hz- litres/sec (cfm)	142 (300)	142 (300)	260 (550)	330 (700)	354 (750)	156 (330)	283 (600)
Airflow 50 Hz- litres/sec (cfm)	118 (250)	118 (250)	212 (450)	283 (600)	295 (625)	106 (225)	236 (500)
Net Weight - kg (lb)	135 (299)	150 (331)	164 (361)	197 (435)	279 (615)	247 (544)	305 (673)
Available Voltages	Non Rev Amps, (Rev Amps)	Non Rev Amps, (Rev Amps)	Non Rev Amps, (Rev Amps)	Non Rev Amps, (Rev Amps)	Non Rev Amps, (Rev Amps)	Non Rev Amps (both pockets)	Non Rev Amps (both pockets)
Gas							
100/200-220/60/1 200/60/1	11.0/5.8 (11.0/5.8)	11.0/5.8 (11.0/5.8)	11.0/5.8 (11.0/5.8)	9.8/4.9 (9.8/4.9)		22.0/11.6 total	11.2 total
120/208-240/60/1 120/60/1	12.0/6.7 (12.0/6.7)	12.0/6.7 (12.0/6.7)	12.0/6.7 (12.0/6.7)	9.2/6.5 (9.2/6.5)	(13/7) 13.8	16.0/8.0 total	
200-208/240/60/1 208-240/60/1					7.6/7.6 (7.6/7.6)		12.0 total
200-208/240/60/3 380/60/3	3.2/3.2 (4.0/4.0) 1.5 (2.0)	3.2/3.2 (4.0/4.0) 1.5 (2.0)	3.2/3.2 (4.0/4.0) 1.5 (2.0)	4.0/3.9 (4.0/4.5) 1.8 (2.1)	3.8/3.8 (4.3/4.3) 1.8 (2.1)	6.4/6.4 total 3.0 total	9.6/9.6 total
460-480/60/3 100/200/50/1 200/50/1	1.6 (2.0) 12.1/7.5 (12.1/7.5)	1.6 (2.0) 12.1/7.5 (12.1/7.5)	1.6 (2.0) 12.1/7.5 (12.1/7.5)	10.0/6.2 (10.0/6.2)	1.9 (2.1)	3.3 total 24.2/15.0 total	11.2 total
230-240/50/1 200/50/3	7.5 2.9 (3.5)	7.5 2.9 (3.5)	7.5 2.9 (3.5)	5.5	6.7 (7.0) 3.5 (4.5)	9.0 total 5.8 total	10.8 total
230-240/50/3 380/50/3	3.5 N/A	3.5 N/A	3.5 N/A		3.5 (4.9)	7.0 total	
400-415/50/3 380/400-415/50/3				2.0 (2.5) 2.0 (2.5)			
Electric	1.5/1.6 (2.0/2.0)	1.5/1.6 (2.0/2.0)	1.5/1.6 (2.0/2.0)		1.8/1.8 (2.1/2.1)	3.0/3.2 total	
200-208/60/3 240/60/3	28 (28) 24 (24)	38 (38) 33 (33)	36 (36) 32 (32)	63 (63) 46 (46)	63 (63) 56 (56)	37 x 2 - 74 total 33 x 2 - 66 total	
380/60/3 440/60/3	15 (15) 13 (13)	20 (20)	20 (20)		33 (33) 28 (28)	20 x 2 - 40 total 17 x 2 - 34 total	
460-480/60/3 480/60/3	12 (12)	16 (16)	16 (16)		27 (27)	16 x 2 - 32 total	
380/50/3 400-415/50/3	15 (15) 13 (13)	19 (19) 18 (18)	20 (20) 18 (18)	29 (29) 27 (27)	34 (34) 32 (32)	19 x 2 - 38 total 18 x 2 - 32 total	
Shipping Weight - kg (lb)	151 (332)	165 (364)	179 (394)	216 (476)	307 (677)	264 (582)	326 (718)
Shipping Width - mm (in)	762 (30)	762 (30)	838 (33)	902 (35 1/2)	1054 (41 1/2)	825 (32 1/2)	902 (35 1/2)
Shipping Depth - mm (in)	1092 (43)	1245 (49)	1245 (49)	1499 (59)	1433 (56 13/32)	1194 (47)	1372 (54)
Shipping Height - mm (in)	1753 (69)	1753 (69)	1753 (69)	1829 (72)	2057 (81)	2057 (81)	2159 (85)
Agency Approvals	CSA, CE	CSA, CE	CSA, CE	CSA, CE	CSA, CE	CSA, CE	CSA, CE

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Printed in the U.S.A.

speedqueen.com/intl

