

## VENDED LAUNDRY

### Softmount Washer-Extractors

6.5 kg (14 lb) Washer-Extractor

8.0 kg (20 lb) Washer-Extractor

11.0 kg (25 lb) Washer-Extractor

14.0 kg (30 lb) Washer-Extractor

18.0 kg (40 lb) Washer-Extractor

24.0 kg (55 lb) Washer-Extractor

28.0 kg (65 lb) Washer-Extractor



# Speed Queen®



# VENDED LAUNDRY SOFTMOUNT WASHER-EXTRACTORS 6.5-28.0 KG – QED CONTROL

MODELS	SY*65	SY*80	SY*105	SY*135	SY*180	SY*240	SY*280	
Control	QED	QED	QED	QED	QED	QED	QED	
Capacity kg (lb)	6.5 (14)	8 (20)	11 (25)	14 (30)	18 (40)	24 (55)	28 (65)	
Tilt Option	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
<b>Dimensions w/o Tilt</b>								
Width mm (in)	710 (27 15/16)	710 (27 15/16)	795 (31 5/16)	795 (31 5/16)	970 (38 3/16)	970 (38 3/16)	970 (38 3/16)	
Depth mm (in)	740 (29 1/8)	790 (31 1/8)	795 (31 5/16)	945 (37 3/16)	970 (38 3/16)	1105 (43 1/2)	1185 (46 5/8)	
Height mm (in)	1115 (43 7/8)	1115 (43 7/8)	1225 (48 1/4)	1225 (48 1/4)	1410 (55 1/2)	1410 (55 1/2)	1410 (55 1/2)	
<b>Dimensions w/ Tilt</b>								
Width mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Depth mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Height mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Cylinder Diameter mm (in)	530 (20 7/8)	530 (20 7/8)	620 (24 3/8)	620 (24 3/8)	750 (29 1/2)	750 (29 1/2)	750 (29 1/2)	
Cylinder Depth mm (in)	305 (12)	350 (13 3/4)	350 (13 3/4)	450 (17 3/4)	410 (16)	545 (21 1/2)	620 (24 1/2)	
Cylinder Volume litres (Cu.ft.)	65 (2.3)	75 (2.6)	105 (3.7)	135 (4.8)	180 (6.4)	240 (8.5)	280 (9.9)	
Door opening size mm (in)	330 (13)	330 (13)	410 (16 1/8)	410 (16 1/8)	460 (18 1/8)	460 (18 1/8)	460 (18 1/8)	
Door Bottom to Floor mm (in)	349 (13 3/4)	349 (13 3/4)	342 (13 1/2)	342 (13 1/2)	477 (18 3/4)	477 (18 3/4)	477 (18 3/4)	
Wash Speed RPM	49	49	49	49	42	42	42	
Extract Speed RPM	1165	1165	1075	1075	980	980	915	
Extract G-Force	400	400	400	400	400	400	350	
Water Inlet Conn. mm (in)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	
Steam Inlet Conn. mm (in)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	
Drain Conn. Size mm (in)	76 (3)	76 (3)	76 (3)	76 (3)	76 (3)	76 (3)	76 (3)	
Motor Size kW (HP)	0.75 (1.00)	0.75 (1.00)	1.10 (1.48)	1.50 (2.01)	2.20 (2.95)	3.00 (4.02)	3.00 (4.02)	
Voltage/Hz/Phase	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph
<b>Shipping Dimensions w/o Tilt</b>								
Height mm (in)	1245 (49)	1245 (49)	1345 (52 15/16)	1345 (52 15/16)	1550 (61)	1550 (61)	1550 (61)	
Width mm (in)	750 (29 1/2)	750 (29 1/2)	835 (32 7/8)	835 (32 7/8)	1025 (40 3/8)	1025 (40 3/8)	1025 (40 3/8)	
Depth mm (in)	825 (32 1/2)	825 (32 1/2)	825 (32 1/2)	970 (38 3/16)	1110 (43 11/16)	1240 (48 13/16)	1390 (54 3/4)	
<b>Shipping Dimensions w/ Tilt</b>								
Height mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Width mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Depth mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Net Weight kg (lb) w/o tilt	170 (375)	185 (408)	210 (463)	255 (563)	380 (838)	430 (948)	495 (1092)	
Net Weight kg (lb) w/ tilt	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Shipping Weight kg (lb) w/o tilt	180 (397)	200 (441)	235 (518)	275 (606)	395 (871)	450 (992)	515 (1135)	
Shipping Weight kg (lb) w/ tilt	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Agency Approvals	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA	

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Czech facility has been registered to ISO 14001:2005 and 9001:2009.

Printed in the U.S.A.

[speedqueen.com/intl](http://speedqueen.com/intl)

