

VENDED LAUNDRY

Heat Pump Tumble Dryers

- 9.0 kg (20 lb) Tumble Dryer
- 11.0 kg (25 lb) Tumble Dryer
- 13.0 kg (30 lb) Tumble Dryer
- 16.0 kg (35 lb) Tumble Dryer

Speed Queen®



VENDED LAUNDRY HEAT PUMP TUMBLE DRYERS 9.0-16.0 KG – EASY CONTROLS

MODELS	SHP*190	SHP*250	SHP*285	SHP*345
Control Options	Easy	Easy	Easy	Easy
Dry Weight Capacity kg (lb)	9 (20)	11 (25)	13 (30)	16 (35)
Cylinder Size - mm (in) (diameter x depth)	760 x 420 (29 15/16 x 16 1/2)	760 x 540 (29 15/16 x 21 1/4)	760 x 630 (29 15/16 x 24 13/16)	760 x 750 (29 15/16 x 29 1/2)
Cylinder Volume - liters (cu.ft)	190 (6.71)	250 (8.83)	285 (10.07)	345 (12.18)
Width - mm (in)	795 (31 5/16)	795 (31 5/16)	795 (31 5/16)	795 (31 5/16)
Depth - mm (in)	1275 (50 3/16)	1525 (60)	1615 (63 9/16)	1735 (68 5/16)
Height mm (in)	1465 (57 11/16)	1680 (66 1/8)	1680 (66 1/8)	1680 (66 1/8)
Door Opening Diameter - mm (in)	600 (23 5/8)	600 (23 5/8)	600 (23 5/8)	600 (23 5/8)
Floor to Door Handle - mm (in)	850 (33 1/2)	1000 (39 3/8)	1000 (39 3/8)	1000 (39 3/8)
Fan Motor - kW (HP)	0.3 (0.4)	0.3 (0.4)	0.3 (0.4)	0.3 (0.4)
Drive Moter - kW (HP)	0.18 (0.24)	0.25 (0.34)	0.25 (0.34)	0.25 (0.34)
Heat Pump Energy Consumption - kW (HP)	2.9 (3.9)	2.9 (3.9)	2.9 (3.9)	2.9 (3.9)
Energy Data - kW (Btu/hr)	3.4 (11612) / 3.6 (12295)	3.4 (11612) / 3.6 (12295)	3.4 (11612) / 3.6 (12295)	3.4 (11612) / 3.6 (12295)
Air Outlet Diameter - mm (in)	Not Applicable for machines with heat pump			
Airflow liters/sec (cfm) 60 Hz	Not Applicable for machines with heat pump			
Airflow liters/sec (cfm) 50 Hz	Not Applicable for machines with heat pump			
Reversing Cylinder	Option	Option	Option	Option
Available Voltages	220-240/50/60/1, 220-240/50/60/3, 380-415/50/60/3+N, 440/50/60/3			
Net Weight - kg (lb)	290 (639)	350 (772)	360 (794)	375 (827)
Shipping Weight - kg (lb)	305 (672)	385 (849)	400 (882)	400 (882)
Agency Approvals	CE	CE	CE	CE

speedqueen.com/intl

